

ACCESSIBILITY · STAINLESS GRAB BARS

STAINLESS GRAB BARS

18" · 36" · 48"

Heavy-duty 1-1/2" stainless grab bars with concealed flanges and welded construction. Polished finish standard, powder coating on request.

18"



36"



48"



250 lb	1-1/2" OD	1-1/2"	ADA
RATED LOAD, PROPERLY MOUNTED	18 GA STAINLESS TUBE	WALL CLEARANCE	ADAAG · ANSI A117.1 · UFAS

OVERVIEW

These grab bars give Portland Loo users a solid handhold at the toilet and along the wall. All three lengths, 18", 36" and 48", use the same tube, flanges and finish, so one spec sheet covers all of them.

Each bar is a single mandrel-bent stainless tube welded through its mounting flanges. Snap-on escutcheons cover the mounting screws, so no fasteners are exposed to tampering. Polished is the standard finish, and a powder-coated color is available on request.

KEY FEATURES

- 01 Welded for strength**
Bent tube ends pass through the flanges and are welded, then ground and polished smooth.
- 02 Concealed mounting**
One-piece 14 ga escutcheons snap over 3" flanges to hide the screws.
- 03 Uniform grip**
The mandrel bending process keeps the full 1-1/2" diameter through the bends.
- 04 Finish options**
Polished stainless standard; powder coated on request.

CONSTRUCTION & SPECIFICATIONS

Model	Bradley 812 Series, 001 straight grab bar
Tubing	1-1/2" O.D., 18 gage stainless steel, seamless; mandrel bent; polished finish
Flanges	3" diameter, 12 gage stainless steel; tube ends pass through and are welded
Escutcheons	14 gage stainless, one-piece drawn; snap over the flanges to conceal mounting screws
Welds	All exposed welds ground and polished to blend
Wall clearance	1-1/2" between wall and bar (required by most building codes)
Load rating	Up to 250 lb when properly mounted; the wall must be reinforced where the bar mounts
Fasteners	General-purpose mounting screws included; use fasteners suited to the wall substrate
Compliance	ADA, ADAAG, ICC/ANSI A117.1, UFAS

SIZES & ORDERING OPTIONS

LENGTH	MODEL	SHIP WEIGHT
18"	812-001, 18" Std	2 lb
36"	812-001, 36" Std	3 lb
48"	812-001, 48" Std	4 lb

OPTION	STANDARD	AVAILABLE ON REQUEST
Finish	Polished stainless Std	Powder coated



Straight bar. Polished stainless, concealed flanges.



Installed. Grab bars inside a Portland Loo.



Flange. The escutcheon hides the mounting screws.

INSTALL TIP — The bar is only as strong as the wall behind it. Mount into reinforced wall areas, use fasteners rated for the substrate, and keep the 1-1/2" wall clearance. Check local accessibility codes for mounting heights and locations.