

SATIN STAINLESS · ADA

# STAINLESS ROBE HOOK

A compact, all-welded stainless hook that gives Loo users a clean place to hang a bag or coat.

**2" × 2"**

FLANGE (50 × 50 MM)

**1-5/8"**

PROJECTION FROM WALL (40 MM)

**Type 304**

SATIN-FINISH STAINLESS

**ADA**

MOUNT 38-40" ABOVE FLOOR



## OVERVIEW

The Bobrick B-76717 surface-mounted robe hook is made of type-304 stainless steel with a satin finish. Its square flange and short, solid hook keep a low profile on the wall, so there's little to grab, bend or snag.

It hangs on a concealed wall plate and is locked in place by a stainless setscrew at the bottom of the flange. There are no exposed screws on the face.

### 01 ALL-WELDED CONSTRUCTION

The 14-gauge cap is welded to the support arm, and the flange and arm are welded to a concealed 18-gauge bracket.

### 03 ACCESSIBLE

ADA compliant. The recommended mounting height for accessible design is 38-40" off the floor.

### 02 CONCEALED MOUNTING

A hidden 19-gauge wall plate and a stainless setscrew hold the hook securely, with no visible fasteners.

### 04 EASY TO CLEAN

Satin stainless wipes clean. Wipe with the grain and avoid bleach and chloride cleaners.

SPECIFICATIONS

|                   |                                                                                                                                        |
|-------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Model             | Bobrick B-76717 surface-mounted robe hook                                                                                              |
| Material / finish | 18-8, type-304 stainless steel, satin finish                                                                                           |
| Construction      | Flange and support arm 22 ga (0.8 mm) · cap 14 ga (2.0 mm), welded to the arm · concealed 18 ga (1.2 mm) mounting bracket · all welded |
| Wall plate        | Concealed 19 ga (1.0 mm) type-304 stainless, secured with a stainless setscrew                                                         |
| Dimensions        | Flange 2" × 2" (50 × 50 mm) · hook 1-5/8" H × 13/16" W (40 × 21 mm) · projects 1-5/8" (40 mm)                                          |
| Mounting height   | 38-40" (965-1015 mm) off the floor for accessible design                                                                               |
| Fasteners         | Two sheet-metal screws furnished for the wall plate                                                                                    |
| Accessibility     | ADA compliant                                                                                                                          |
| Warranty          | 1 year against defects in workmanship and material (Bobrick)                                                                           |

ORDERING OPTIONS

| OPTION | STANDARD                             | AVAILABLE ON REQUEST               |
|--------|--------------------------------------|------------------------------------|
| Finish | <b>STD</b> Satin stainless (B-76717) | Bright polished stainless (B-7671) |

VIEWS



FRONT

Square flange and low-profile hook.



BACK

Concealed mounting bracket and setscrew.



3/4 VIEW

Welded cap on the support arm.

INSTALL & CARE

Screw the wall plate up with its prongs at the top, hook the flange onto the prongs and tighten the setscrew at the bottom. To keep the satin finish looking new, wipe with the grain, rinse off soap residue and avoid bleach, chloride cleaners and steel wool. Light rust spots come off with a stainless polish or a Scotch-Brite #7447 pad.