

TWO-ROLL · LOCKING

TOILET TISSUE DISPENSER

A locking, two-roll stainless dispenser that keeps a spare roll ready so the Loo doesn't run out.

2 rolls

UP TO 1,800 SHEETS

5-1/4"

MAX ROLL DIAMETER (133 MM)

Type 304

SATIN STAINLESS, ALL WELDED

Lock & key

THEFT-RESISTANT SPINDLES

OVERVIEW

The Bobrick B-2888 surface-mounted multi-roll dispenser holds two standard-core rolls. When the bottom roll runs out, the spare automatically drops into place, so users aren't left without paper between service visits.

The rolls lock into the stainless dispensing mechanism behind a seamless, drawn stainless door with a tumbler lock. The spindles stay captive while the door is locked, and empty cores can only be removed by unlocking it.

01 AUTOMATIC RESERVE ROLL

The extra roll drops in place as soon as the bottom roll is used up.

03 TOUGH, ALL-WELDED BODY

Type-304 stainless cabinet and an 18-gauge stainless dispensing mechanism, inner housing and cam.

02 THEFT-RESISTANT SPINDLES

Heavy-duty, one-piece molded ABS spindles are held in the mechanism while the door is locked.

04 ONE KEY FOR THE CREW

The tumbler lock is keyed like other Bobrick washroom accessories. ADA compliant when mounted at the right height.

**SERVICE TIP**

Load both rolls at each visit: the spare drops in on its own when the bottom roll runs out. Empty cores and spindles come out only with the key, which helps cut down on theft and vandalism.

SPECIFICATIONS

Model	Bobrick B-2888 surface-mounted multi-roll toilet tissue dispenser
Cabinet	18-8, type-304, 22 ga (0.8 mm) stainless, all welded, satin finish
Door	22 ga type-304 stainless with an 18 ga (1.2 mm) frame · drawn, one-piece, seamless front · secured with two rivets · tumbler lock and key
Mechanism	Dispensing mechanism, inner housing and cam in 18 ga (1.2 mm) type-304 stainless
Spindles	Two heavy-duty, one-piece molded ABS · theft resistant, retained while the door is locked
Capacity	Two standard-core rolls up to 5-1/4" (133 mm) diameter · 1,800 sheets
Dimensions	6-1/16" W × 11" H × 5-15/16" D (154 × 279 × 151 mm)
Weight	11.66 lb
Mounting	Surface mounted with four #10 sheet-metal screws or through-bolts (fasteners not furnished by Bobrick)
Warranty	1 year against defects in workmanship and material (Bobrick)

ACCESSIBLE MOUNTING HEIGHTS

STANDARD	RECOMMENDED MOUNTING HEIGHT OFF FLOOR	MIN. HEIGHT OF OPERABLE PART*
ADA	25-3/4" (655 mm)	15" (381 mm)
ICC	28-3/4" (730 mm)	18" (457 mm)
California (CBC)	29-3/4" (755 mm)	19" (483 mm)

*Operable part = bottom of the tissue opening, measured above the finished floor (Bobrick technical data, rev. 4/8/26).

VIEWS



FRONT
Seamless locking door with key.



BACK
Keyhole slots and mounting holes.



SPINDLE
Heavy-duty molded ABS (2 per unit).