REPLACEMENT PART HAND WASH · SOAP

Gravity-Flow Soap Dispenser Valve

The chrome-plated push valve that delivers soap from the Loo's gravity-fed soap supply, with a 3/8" NPT male connection.



3/8" NPT	Brass	3-1/2"	V1 Classic
MALE PIPE THREAD	CHROME-PLATED BODY	OVERALL LENGTH	XL BY REQUEST

OVERVIEW

This is the soap valve used on the Portland Loo V1 Classic, and on the V2 XL by request. Soap flows by gravity to the valve, so there's no pump or batteries. A press of the button dispenses soap.

When a valve wears out or gets damaged, swap it for a new one to keep the hand-wash station working. We recommend installing a fresh set of fittings with it: a low-pressure stainless NPT fitting, a barbed NPT elbow and an NPT locknut.

KEY FEATURES

01 Gravity fed
No pump, power or batteries. Soap flows to the valve on its own.

02 Push-button operation
A simple press dispenses soap at the hand-wash station.

03 Chrome-plated brass
A solid metal body with a bright, easy-to-clean chrome finish.

04 Standard 3/8" NPT
A male pipe-thread connection matches the original valve and fittings.

CONSTRUCTION & SPECIFICATIONS

Dispenser type	Gravity flow, push-button valve
Material	Chrome-plated brass
Connection	3/8" NPT male pipe thread
Overall length	3-1/2"
Fits	Portland Loo V1 Classic (standard); V2 XL by request only
Recommended with	New low-pressure stainless NPT fitting, barbed NPT elbow and NPT locknut

ORDERING OPTIONS

OPTION	STANDARD	AVAILABLE ON REQUEST
Valve	Gravity-flow valve, chrome-plated brass, 3/8" NPT male STD	—
Model	V1 Classic STD	V2 XL
Replacement fittings	—	Stainless NPT fitting, barbed NPT elbow and NPT locknut (recommended)


RECOMMENDED REPLACEMENT FITTINGS



Stainless NPT fitting
Low pressure, female NPT



Barbed NPT elbow
90°, male NPT to hose barb



NPT locknut
3/8" NPT

ORDERING TIP

Replacing the valve? Order the three fittings with it. Old fittings can be worn or corroded, and a fresh set gives you tight threads and a leak-free soap line. Tell us whether your restroom is a V1 Classic or a V2 XL.