REPLACEMENT PART LIGHTING CONTROL

FSP-L2 LENS MODULE

A white polycarbonate lens that fits over the Wattstopper FSP-202 and FSP-212 motion sensors. It cuts down on false triggers from busy city streets and from the weather.



2.33"	0.79"	0.47 oz	In / Out
Diameter	Depth	Weight	Rated for indoor and outdoor use

OVERVIEW

The FSP-L2 is the lens module for the Wattstopper FSP-202 and FSP-212 fixture-integrated sensors. It sets the sensor's field of view, so the lights respond to people using the Loo and not to traffic, passersby or blowing rain beyond it.

That matters for restrooms in dense city locations, where a wide-open sensor can keep the lights cycling all night. The FSP sensor ships without a lens, so order the FSP-L2 with every replacement sensor, or on its own to replace a cracked or weathered lens.

KEY FEATURES

01 **Fewer false triggers**
Narrows what the sensor sees, cutting nuisance triggers from street activity and the weather.

02 **Made for FSP sensors**
Fits the Wattstopper FSP-202 (low voltage) and FSP-212 (line voltage) sensors.

03 **Weather ready**
Rated for indoor and outdoor use. White gloss polycarbonate stands up to sun and impact.

04 **Easy to replace**
A small, light lens module (2.33" across, under half an ounce) that comes with Wattstopper's 5-year warranty.

SPECIFICATIONS

ITEM	DETAIL
Model	Wattstopper (Legrand) FSP-L2 lens module
Compatibility	Wattstopper FSP series fixture sensors: FSP-202 (low voltage) and FSP-212 (line voltage)
Purpose	Limits the sensor's field of view to reduce false triggers in dense city locations and from weather
Coverage	For an 8 ft mounting height, about 48 ft coverage diameter (per the Wattstopper FSP spec sheet)
Material / finish	Polycarbonate, white, gloss
Dimensions	2.329" W x 2.329" H x 0.791" D
Weight	0.472 oz
Environment	Indoor and outdoor. With the lens fitted, the FSP sensor is rated IP66 when mounted in the fixture.
Compliance	RoHS compliant
Warranty	5 years from Wattstopper

ORDERING OPTIONS

OPTION	STANDARD	AVAILABLE ON REQUEST
Lens	FSP-L2, white STD	—
Sold	Each, lens only STD	With a replacement FSP-202 sensor

VIEWS



Angled view. The faceted lens dome and its four locating tabs.



Face view. The side that faces into the restroom.



Back. The mounting collar that fits onto the sensor, with the Wattstopper FSP-L2 label.

ORDERING TIP

FSP sensors ship without a lens. Order an FSP-L2 with every replacement FSP-202 sensor, and keep a spare lens on hand to replace one that's cracked, chalky or weathered.